



COMMUNITY'S PATENTED COOL-COIL™ TECHNOLOGY



Cool Air Sucked In

The voicecoil remains significantly cooler, and as a result is subsequently able to handle much greater power.



Power Robbing Hot Air Forced Out

With an inherent ability to thermally draw destructive heat away from a loudspeaker's voicecoil, Community's new patented Cool-Coil™ technology creates a cooling, self-sustained airflow which is directed onto the voicecoil's tubular former.



IntelliSense™ PROTECTION

Every cabinet of the Tandem Drive Series is protected by IntelliSense™ and PowerMeter™ circuitry. PowerMeter LED indicators flash green to indicate signal presence, yellow to warn that the loudspeaker has entered the first safeguarding stages of IntelliSense™ protection, and red to show that full protection has been applied. Once power has been reduced, the circuit resets itself, restoring full efficiency.

Community

PROFESSIONAL LOUDSPEAKERS

333 East 5th Street, Chester, PA USA 19013-4511
TEL: (610) 876-3400 · (800) 523-4934 · FAX: (610) 874-0190
www.loudspeakers.net

TDBROCH-1103



MOUNT THEM, STACK THEM, FLY THEM

Mounting poles offered for use with each Tandem Drive subwoofer system allow complete, freestanding systems to be effortlessly assembled using the cabinet's 1-3/8" pole sockets.

OPTIONAL ACCESSORIES

Model # SB5	5 ft. steel mounting pole for mounting a Tandem Drive full-range cabinet on TD2118 subwoofer
Model # MP33	33.5 inch mounting pole for mounting a Tandem Drive full-range cabinet on TD2115 subwoofer
Model # CASTERS 4	Kit of 4 heavy-duty 4" casters for TD2118
Model # STRAPKIT	3 steel straps with a series of 3/8" / 10 mm diameter holes for attaching rigging to threaded inserts. Use with all TD except TD2118.



THE TANDEM DRIVE SYSTEM IS UNIQUE

Each two-way, full-range TD2212 and TD2215 employs Community's UC1 ferrofluid-cooled high frequency driver and dual Cool-Coil™ woofers. These dual woofers, one front and one down firing, give extended low frequency response and efficiency in a compact sized enclosure.

TANDEM DRIVE

LOUDSPEAKER SERIES



with
Cool-Coil™ LF Technology
and **IntelliSense™ Protection**

Community

PROFESSIONAL LOUDSPEAKERS

THE TANDEM DRIVE LOUDSPEAKERS FROM COMMUNITY

Power and performance above the rest.

Used to be sound this big required a tractor-trailer rig and roadies to move from place-to-place. Kiss those days good-bye, because now the Tandem Drive Series loudspeakers from Community let you pack a serious sonic punch without shouldering the weight of the world.

Optionally, add one of the two subwoofers as building blocks to create a DJ, corporate, house of worship, or live performance system tailored expressly to your application's needs. Steel mounting poles allow the TD2212 or TD2215 to top-off either of the subs for extended-range fidelity and the height to project above the crowd.

Constructed from lightweight plywood, each Tandem Drive loudspeaker enclosure is sealed with Tuf-Coat™, a virtually indestructible finish with an amazingly high resistance to dents, dings,

scratches, and the abuses of regular manhandling. Inside each box, proprietary low frequency drivers feature Community's patented Cool-Coil™ technology. And to keep you up-and-running no matter how loud it gets, every model is internally safeguarded with IntelliSense™, a multi-stage protective circuit which guarantees maximum output minus the risk of speaker damage.

Built to perform night-after-night without missing a beat, Tandem Drive components deliver raw acoustic power and unrivaled sonic clarity, all in packages backed by a full five-year warranty. At Community, we listen, then build the products you want. Go hear the difference.

THE NEXT STEP IN PERFORMANCE

SPECIFICATIONS

	TD2212**	TD2215**	TD2115	TD2118
Drivers	LF 2 x 12", HF 1 x non-metallic UC1*	LF 2 x 15", HF 1 x non-metallic UC1*	2 x 15"	2 x 18"
Frequency Response	80Hz-16kHz (+/-4dB)	60Hz-16kHz (+/-4dB)	45-160Hz (+/-2dB)	40-150Hz (+/-4dB)
Power Handling (RMS)	300W	400W	400W	600W
Program	750W	1000W	1000W	1500W
Sensitivity 1W/1m	97dB SPL	97dB SPL	95dB SPL	95dB SPL
Maximum SPL (1M)	123 dB SPL / 130 dB SPL (peak)	123 dB SPL / 130 dB SPL (peak)	121 dB SPL / 128 dB SPL (peak)	123 dB SPL / 130 dB SPL (peak)
Nominal Impedance	4 Ohm	4 Ohm	4 Ohm	4 Ohm
Nominal Dispersion	90°H x 40°V	90°H x 40°V	N/A	N/A
Crossover Frequencies	2kHz Passive or Bi-amp	2kHz Passive or Bi-amp	Internal 150 Hz High Pass Filter	Internal 150 Hz High Pass Filter
Input Connection	2 x NL4 / 2 x 1/4"	2 x NL4 / 2 x 1/4"	2 x NL4 / 2 x 1/4"	2 x NL4 / 2 x 1/4"
Height	25" (637mm)	27" (683mm)	33" (842mm)	25" (638.8mm)
Width	14" (353mm)	17" (438.9mm)	17" (438.9mm)	40" (1016mm)
Depth	18" (448mm)	20" (505mm)	22" (556mm)	24" (603mm)
Weight lb. (kg.)	49 lbs. (22 kg.)	71 lbs. (32.2 kg.)	92 lbs. (41.7 kg.)	144 lbs. (65.3 kg.)
Shipping Weight lb. (kg.)	60 lbs. (27.2 kg.)	80 lbs. (36.3 kg.)	105 lbs. (47.6 kg.)	160 lbs. (72.6 kg.)

* ferrofluid-cooled
** flyable

TD2212**

TD2215**

SUBWOOFERS

TD2115

TD2118

FULLRANGE

TD2212

TD2215



MORE BASS-LESS SPACE-MORE BASS-LESS SPACE-MORE BASS

PRODUCT DESCRIPTIONS:

TD2212

At 49 pounds, the TD2212 is the lightest and most compact loudspeaker within the Tandem Drive Series. The system is a two-way design, housing dual 12-inch Cool-Coil™ woofers, Community's Ferrofluid-cooled UC1 high frequency driver and a switchable bi-amp or full-range internal crossover with built-in presence curves. It is perfect for smaller systems. The TD2212 can be pole-mounted for combined use with either the TD2115 or TD2118 subwoofer.

TD2215

High power handling and sensitivity make the TD2215 ideally suited for high-SPL environments. Equipped with dual 15-inch Cool-Coil™ low frequency drivers, the TD2215 shares the same horn-loaded, 90°x40° UC1 high frequency section as the TD2212, with switchable presence curves. Outfitted with a non-metallic diaphragm to increase internal dampening, reduce ringing, and provide more accurate response as well as extremely low distortion, the low-mass high frequency driver is ferrofluid cooled to dissipate heat quickly and keep you running wide open all night long. The TD2215 can also be stand mounted, or pole-mounted with TD2115 or TD2118 subwoofers.

TD2115

Dual 15-inch Cool-Coil™ drivers are central to the solid bass performance stored within the TD2115. Remarkably portable in relation to the size of its rich, full sound; the cabinet delivers enough low frequency energy to reliably bring down the house on any occasion.

TD2118

With extended low frequency performance capable of dropping into seismically uncharted territory, this—the largest of the Tandem subs—packs dual 18-inch Cool-Coil™ drivers into a vented cabinet. Optional four heavy-duty casters allow the TD2118 to hit the road.